

1/4" NPT PORT
for PRESSURE
TRANSDUCER

RELEASE VALVE LEVER

MOVEMENT

1. DESCRIPTION- 10 TON INTEGRAL CYLINDER / PUMP UNIT, UNIVERSAL ORIENTATION. SEALED HYDRAULICS, TWO SPEED ORIENTATION, AUTO CHANGEDOVER, SARUM CODE
2. WP 400 BAR, BUILT IN RELIEF VALVE SET 700 BAR, EXTERNALLY ADJUSTABLE
3. OPERATING FLUID MINERAL OIL. CONSULT FACTORY IF IN DOUBT
4. MASS 5KG APPROX
5. OPERATING TEMPERATURE RANGE -20 TO +50°C
6. MATERIALS OF CONSTRUCTION
CARBON STEEL BS970, STAINLESS STEEL 302, 303, 304, 316, 420, BRONZE ZC307G. LOW CORROSION FINISH ON PUMP BODY AND PISTON ROD
SEALS PTFE AND NITRILE
7. DIMENSIONS IN MM
8. DRAWING 134000200 IS SAME DRAWING

360 DEGREE SWIVEL
ON HANDLE

RAM EXTENDED

SARUM

P.O. BOX 48, SALISBURY SP1 3YB
TEL. 01722 328388 FAX. 01722 414307

FINISH	SEE NOTE
--------	----------

MV-10

FORM REF. SHBDR ISS.A